

CONFIDENTIAL

VERTRAULICH

THIS DRAWING IS THE EXCLUSIVE PROPERTY OF MARQUARDT. WITHOUT THEIR CONSENT IT MAY NOT BE REPRODUCED OR GIVEN TO THIRD PARTIES.

Alle Rechte bei Marquardt, auch fuer den Fall von Schutzrechtsanmeldungen. Jede Veruegungsbefugnis, wie Kopier- und Weitergaberecht, bei uns.

	1	2	3	4	
A	recommended cut-out for snap-in fixing (edge opposite to snap-in direction)		wall thickness	length of cut-out	width of cut-out
			0.75 to 1.25	19.2-0.1	12.9+0.1
			1.25 to 2	19.4-0.1	12.9+0.1
		2 to 3	19.8-0.1	12.9+0.1	

  

drawn in "ON" position

**Marking**

Ⓜ

18..

6(4)/250~5E4

10(4)/250~ T100/55

5/50A 250V~

---

6A 125-250V AC

1/4 HP 125V AC

1/2 HP 250V AC

R 30

Code of manufacture: place /year/week

On box: G

SPST

Suitable for appliances of class II

Rocker and Housing V0-material

G= matching IEC 60335-1 :2001 clause 30

-	-	-	1801.1912-XX
Figure	Type	Customer Part No.	Art.No.-PI
Shape and location	Angle ± 2 °	Sheet 01	
	Edge tolerance	Ident. K	Document number 18011912
⊙ ≡	Length	Projection	Index d
	Radii	Scale 1:1	Appliance Switch
0-6 ± 0.2	All dimensions are in millimetres		
>6-15 ± 0.4	System NX V1872		
>15-30 ± 0.4	Replacement of		
>30-70 ±	Zg.gl.Nr.v.07.07.1998		
±	Edited by		
d 137838	2021-08-13	MOHITEN	
c 61758	2009-01-12	MUT	
b 47092	2006-05-11	MUT	
a 43724	2005-07-20	vor	
Index	MEC-No.	Date (YYYY-MM-DD)	Edited by