

1		2		3		4	
Empfohlener Plattenausschnitt suggested panel cutout		Plattendicke panel thickness 0.75-1.25 1.25-2.00 2.00-3.00		X 21.2 -0.1 21.4 -0.1 21.8 -0.1			
A		B		C		D	
				Flachstecker aehn- plug-in sim. DIN 46 244-A4.8-0.8			
		schwarz black		Wippe schwarz Zeichen weiss rocker black symbol white			
Aufschrift Marking Ⓜ 18.. 8(181/250~5E4 12(41/250~ 5/70A 250V~ T100/55 05 R149 cULus		Aufschriftbeschreibung marking description R149: 15A 125-250V AC 3/4 HP 125V AC 1 1/2 HP 250V AC		Ausschalter 1-polig fuer Ger- aete der Klasse II geeignet SPST suitable for appliances of class II			
fuer Form und Lage FOR SHAPE AND LOC. fuer Winkel FOR ANGLE		⊙ = PROJEKTION Abmasse und Nennmassbereiche Angaben in mm ALL DIMENSIONS ARE IN MILLIMETRES		Loenge LENGTH Radien RADIUS		Pause COPY Blatt SHEET Original Din A4 Masstab SCALE 1:1 30mm	
0-6 ± 0.2 ± 0.2 >6-15 ± 0.4 ± 0.4 >15-30 ± 0.4 ± 0.4 >30-70 ± >70-120 ± >120-200 ±		± 10%		0 10 20 30mm		TYP Zeichn./DRAWING NO. Index K 18811103 c	
c 54873 10/26/07 LX b 45331 02/17/06 MUT a 45770 02/09/06 MUT 43798 10/05/05 MUT		CAD: NX V4.0 gez./DRAWN BY 07/08/05 YLJ gepr./CHECKED BY		GERAETESCHALTER APPLIANCE SWITCH		Ⓜ MARQUARDT	
Ausg. ISSUE Aenderung REVISION gez. DRAWN BY		Ausg. ISSUE Aenderung REVISION gez. DRAWN BY		Ersatz fuer/REPLACEMENT OF V05140100			