

1		2		3		4	
A	Empfohlener Plattenausschnitt suggested panel cutout		Plattendicke panel thickness		X		
			0.75-1.25		21.2 -0.1		
			1.25-2.00		21.4 -0.1		
			2.00-3.00		21.8 -0.1		
B					Flachstecker aehnli. plug-in sim. DIN 46 244-A4.8-0.8		
C							
D							
E	Aufschrift Marking		Aufschriftbeschreibung marking description		Ausschalter 1-polig Fuer Geræete der Klasse II geeignet SPST suitable for appliances of class II		
	18.. 8(81)/250~5E4 12(41)/250~ 5/70A 250V~ T100/55 05		RI49= 15A 125-250V AC 3/4 HP 125V AC 1 1/2 HP 250V AC				
	RI49						
			Allgemeintoleranzen UNTOLERANCED DIMENSIONS		Pause COPY		
			Abmasse und Nennmassbereiche Angaben in mm		Blatt SHEET		
			Loenge LENGTH		01		
			Radien RADIUS		Original		
			0-6 ± 0.2 ± 0.2		Masstab		
			>6-15 ± 0.4 ± 0.4		Din		
			>15-30 ± 0.4 ± 0.4		SCALE		
		>30-70 ±		1:1			
		>70-120 ±		30mm			
		>120-200 ±					
		ALL DIMENSIONS ARE IN MILLIMETRES		0 10 20			
				CAD: NX V2.0			
				gez./DRAWN BY 10/06/05 MUT			
				gepr./CHECKED BY			
				Ersatz fuer/REPLACEMENT OF V05140300			