

	1	2	3	4
A	Empfohlener Ausschnitt fuer Rastbefestigung (Graf gegenueber Bestueckungsseite recommended cut-out for snap-in fixing (edge opposite to snap-in direction)	Wanddicke wall thickness 0.75 bis / to 1.25 1.25 bis / to 3	Ausschnittlaenge length of cut- out 30 ^{-0.1} 30.2 ^{-0.1}	Ausschnittbreite width of cut-out 22 ^{+0.2} 22 ^{+0.2}
B	Die in unseren Unterlagen angegebene IP Schutzklasse bezieht sich auf die Betaetigungsseite des Schalters, wenn dieser in das Kundengerat eingebaut ist. Die Abdichtung zwischen Schalter und Kundengerat kann ueber die umlaufende Dichtlippe der Betaetigungskappe erfolgen. Die Montage in das Kundengerat und die Pruefung auf Dichtheit an dieser Stelle erfolgen kundenseitig. Schalter mit beschaedigten Betaetigungskappen muessen sofort ausgetauscht werden.			
C	The IP-protection class mentioned in our documents refers to the actuating side of the switch when mounted into the customer appliance. The sealing between switch and customer appliance is realizable through the surrounding sealing lip of the actuating cap. The mounting into the customer appliance and the testing of the tightness have to be effected by the customer. Switches with damaged actuating caps have to be replaced immediately.			
D	Ausschalter 2-polig Fuer Geraete der Klasse II geeignet Aufschrift Marking 193.. 20141A 250V AC 10181A 250V AC 5E4 T100/55 15 15000 557791 1 1 2 Herstellort/-jahr/-woche code of manufacture:place/year/week Auf Verpackung / on box:G			
E	DPST suitable for appliances of class II G=Konform nach IEC 60335-1:2001 Kap. 30 G=matching IEC 60335-1:2001 clause 30			

-	-	-	1932.3131-XX
Figure	Type	Customer Part No.	Art.No.-PI
Shape and location	Angle ± 2 ° Edge tolerance	Length Radii	Sheet 01 Format DIN A4 Projection Scale 1:1 All dimensions are in millimetres System NX V2007 Replacement of V09033003
Ident.	Document number	Index	
K	19323131	a	
Appliance switch			
MARQUARDT			