

	1	2	3	4	
A	Empfohlener Ausschnitt fuer Rastbefestigung (Graf gegenueber Bestueckungsseite) <i>recommended cut-out for snap-in fixing ledge opposite to snap-in direction</i>		Wanddicke <i>wall-thickness</i>	Ausschnittlaenge <i>length of cut-out</i>	Ausschnittbreite <i>width of cut-out</i>
			0.75 bis / to 1.25 1.25 bis / to 3	30 ^{+0.1} 30.2 ^{+0.1}	22 ^{+0.2} 22 ^{+0.2}
Die in unseren Unterlagen angegebene IP Schutzklasse bezieht sich auf die Betaetigungsseite des Schalters, wenn dieser in das Kundengerat eingebaut ist. Die Abdichtung zwischen Schalter und Kundengerat kann ueber die umlaufende Dichtlippe der Betaetigungskappe erfolgen. Die Montage in das Kundengerat und die Pruefung auf Dichtheit an dieser Stelle erfolgen kundenseitig. Schalter mit beschaedigten Betaetigungskappen muessen sofort ausgetauscht werden.					
<i>The IP-protection class mentioned in our documents refers to the actuating side of the switch when mounted into the customer appliance. The sealing between switch and customer appliance is realizable through the surrounding sealing lip of the actuating cap. The mounting into the customer appliance and the testing of the tightness have to be effected by the customer. Switches with damaged actuating caps have to be replaced immediately.</i>					
B					
C					
D					
E	Aufschrift <i>Marking</i> 193.. 6(4)A 250V AC 5E4 10(4)A 250V AC 1E4 T100/55 Herstellort/-jahr/-woche <i>code of manufacture: place/year/week</i>				
Umschalter 2-polig Fuer Gerate der Klasse II geeignet DPDT <i>suitable for appliance of class II</i>					

-	-	-	1934.2114-XX
Figure	Type	Customer Part No.	Art.No.-PI
Shape and location 	Angle ± 2 ° Edge tolerance 	Sheet 01 Format DIN A4 Projection Scale 1:1 All dimensions are in millimetres	
		Ident. K	Document number 19342114
		Index g	
		Appliance Switch	
g	140246	2021-11-10 HHE	
f	82477	2013-03-26 ZO	
e	60808	2008-10-27 HHE	
d	59139	2008-07-23 HHE	
Index	MEC-No.	Date (YYYY-MM-DD)	Edited by
System NX V1872		Replacement of Zng.gl.Nr. vom 07.10.05	