

	1	2	3	4	
A	Empfohlener Ausschnitt fuer Rastbefestigung (Grat gegenueber Bestueckungsseite recommended cut-out for snap-in fixing ledge opposite to snap-in direction)		Wanddicke wall thickness 0.75 bis / to 1.25 1.25 bis / to 3	Ausschnittlaenge length of cut-out 30 ^{-0.1} 30.2 ^{-0.1}	Ausschnittbreite width of cut-out 22 ^{+0.2} 22 ^{+0.2}
B	Die in unseren Unterlagen angegebene IP Schutzklasse bezieht sich auf die Betaetigungsseite des Schalters, wenn dieser in das Kundengerat eingebaut ist. Die Abdichtung zwischen Schalter und Kundengerat kann ueber die umlaufende Dichtlippe der Betaetigungskappe erfolgen. Die Montage in das Kundengerat und die Pruefung auf Dichtheit an dieser Stelle erfolgen kundenseitig. Schalter mit beschaedigten Betaetigungskappen muessen sofort ausgetauscht werden.				
C	The IP-protection class mentioned in our documents refers to the actuating side of the switch when mounted into the customer appliance. The sealing between switch and customer appliance is realizable through the surrounding sealing lip of the actuating cap. The mounting into the customer appliance and the testing of the tightness have to be effected by the customer. Switches with damaged actuating caps have to be replaced immediately.				
D					
E	Aufschrift Marking (M) 193.. 12(4)A 250V AC T100/55 μ Umschalter 2-polig Ausstellung in der Mitte Tastfunktion beidseitig Fuer Geraete der Klasse II geeignet DPDT with centre-off biased from both side suitable for appliances of class II				

-	-	-	1939.3312-XX
Figure	Type	Customer Part No.	Art.No.-PI
Shape and location		Sheet 01	Ident. Document number Index
Angle ± 2 °		Format DIN A4	K 19393312 b
Edge tolerance		Projection	
Length		Scale 1:1	
Radii		All dimensions are in millimetres	Appliance switch
b 156485		System NX V2007	MARQUARDT
a 59141		Replacement of	
36431		Zng.gl.Nr. vom 30.06.03	
Index			
MEC-No.		Date (YYYY-MM-DD)	
		Edited by	